

RTU5025

GPRS/3G Gate Opener

The RTU5025 is an upgraded version of famous RTU5015 gate opener, a very simple device which can be used for remote control swing or sliding gates and doors or switching devices with authorized access management(Caller-ID),well used on door access, gate control, remote switching, or car parking systems. Actually the RTU5025 can be used in places which require to turn ON/OFF your system, machines, equipments remotely with a **FREE** phone call from your mobile or fixed line telephone.

PC software for programming via USB,remote server system over TCP/IP supported*,users can easily download the access historical data anywhere anytime.



Advantages

- GSM or 3G band,distribute worldwide applications;
- Up to 999 authorized phone numbers can be configured at the specified time for access control;
- No call charges.Reject calls from authorized number then carries out the turn ON/OFF action on the first 'ring';
- Secure – Using Caller-ID for verification, unknown phone calls are ignored;
- SMS confirmation of relay actions(door open) to the owner or authorized caller number.
- No need remote control or keys for different users;
- Up to 10,000 events log,download the operation historical dat by USB or over GPRS;
- Multiple applications. (gates, bollards, barriers, garage doors, shutters and access doors or machines);

Digital Inputs

- One Digital input for motion sensor or other sensors to protect your door and windows,SMS alert to owner immediately when triggered;
- One Digital input special for secure door and automatically armed when door closed, SMS alert to owner immediately when door opened illegally.

Setting

- SMS command or PC Software programming;
- Operate from anywhere anytime, no distance limitation;

Order Table

| | |
|-----------|--|
| RTU5025: | GSM 850/900/1800/1900MHz |
| RTU5025W: | 2G: GSM900/1800MHz, 3G WCDMA : 900/2100MHz UMTS |
| RTU5025C: | 2G: GSM850/900/1800/1900MHz, 3G: 850/1900MHz UMTS |

Specifications

| | |
|--------------------|--|
| GSM Frequency | Quad-band 850/900/1800/1900MHz |
| 3G Band | 900/2100MHz default 850/1900MHz optional* |
| Digital Input | 2 NC/NO dry contact |
| Digital Output | 1 Relay, 3A/240VAC |
| Siren Output | 12VDC/1A |
| DC Power supply | 9-24VDC/2A |
| Power consumption | 12V input Max. 50mA/Average 50mA |
| SIM Card | Supporting 3V SIM Card |
| Antenna | 50 Ω SMA Antenna interface |
| Temperature range | -20~+60 °C |
| Humidity range | Relative humidity 90% |
| Backup battery | 3.7V/900mAH |
| Exterior dimension | W151mm*D74mm*H27mm |
| Net Weight | 260 g |



Packing List

- Gate Opener * 1
- Antenna * 1
- AC/DC Power adaptor *1,
- User Manual & PC Software CD x1
- Packing size: 19*14*6 cm Gross Weight: 0.75kg 15pos per Carton.
- Optional Accessories:** Door contact sensor, Motion detector, Temperature sensor and others.